

Atlas Lighting Supply
 2828 S. Linwood St
 Visalia, CA 93277
 Ph: 559-697-6764, F: 888-605-2324
 www.atlaslightingsupply.com

E-BAL-S015S	
Ballast Type	High Pressure Sodium
Lamp	150W S55
Circuit Type	R-NPF
Input Frequency	60HZ

Model_No:	E-BAL-S015S			Capacitor (Not Required)	
Input Voltage	120			Capacitance	
Operating Current	4.5			Minimum Volts	
Open Circuit Current	5.13			Dry	Diameter
Starting Current	5.3				Height
CCF (*ANSI≤1.8)	1.8			Case Max. Temperature	
Short Circuit Current	Secondary	5.3			
	Input	5.13			
Recommended Fuse	15			Ignitor (Required)	
Input Voltage At Lamp Dropout				Ignitor Model	IGN-01
UL 1029 Bench Top Rise	A			Pulse Height(kV)	2.5~4.0
	OCV(Min.)	110		Pulse Width (≥u S)	1us@ 2250V
	Input Power	170W			
	Power Factor	0.3-0.5			
Regulation	Line Volts	±5%			
	Lamp Watts	±10%			
Insulation System	Class H, 180°C				
Ballast Dimension	A	1.97"			
Ballast Net Weight	3.4 lbs				
Leads	12"-Cross Link Polyolefin			Min.Starting Temp.	-20°F / -30°C

Ballast Dimension	Wiring Diagram
Ignitor	

When Ordering, add suffix for options:

D - with distributor replacement kit (include bracket, capacitor and ignitor as necessary)

Specifications are subject to change without notice.