

Atlas Lighting Supply
 2828 S. Linwood St
 Visalia, CA 93277
 Ph: 559-697-6764, F: 888-605-2324
 www.atlaslightingsupply.com

E-BAL-H250-A4860N	
Ballast Type	Metal Halide
Lamp	250W M58
Circuit Type	CWA
Input Frequency	60HZ

Model No:	E-BAL-H250-A4860N			Capacitor (Required)		
Input Voltage	480			Capacitance	15uF±3%	
Operating Current	0.7			Minimum Volts	400V	
Open Circuit Current	0.65			Dry	Diameter	1.56"
Starting Current	2.5				Height	3.06"
CCF (*ANSI≤1.8)	1.8			Case Max. Temperature		100°C
Short Circuit Current	Secondary	2.5		Ignitor (Not Required)		
	Input	0.85		Ignitor Model		
Recommended Fuse	2			Pulse Height(kV)		
Input Voltage At Lamp Dropout				Pulse Width (≥u S)		
UL 1029 Bench Top Rise	B					
OCV(Min.)	270					
Input Power	295W					
Power Factor	≥90%					
Regulation	Line Volts	±10%				
	Lamp Watts	±10%				
Insulation System	Class H, 180°C					
Ballast Dimension	A	1.7"				
	B	3.2"				
Ballast Net Weight	10.4 lbs					
Leads	12"-Cross Link Polyolefin			Min.Starting Temp.	-20°F / -30°C	

Ballast Dimension	Wiring Diagram
	Capacitor

When Ordering, add suffix for options:
 D - with distributor replacement kit (include bracket, capacitor and ignitor as necessary)

Specifications are subject to change without notice.