

PS30U242M

Programmed Rapid Start Electronic Fluorescent Ballast Specifications

Line Volts	Lamp Type	#	Input Watts*	Nominal Line Amps	Ballast Factor	Power Factor	THD	Crest Factor
120	CFM42W	2	91	0.76	.98	> 0.98	< 10%	<1.6
277		2	90	0.32	.98	> 0.98	< 10%	<1.6
120	CFM42W	1	45	0.40	1.00	> 0.93	< 10%	<1.6
277		1	45	0.18	1.00	> 0.93	< 10%	<1.6
120	CFM57W	1	58	0.52	1.00	> 0.98	< 10%	<1.6
277		1	57	0.21	1.00	> 0.98	< 10%	<1.6
120	CFM70W	1	73	0.61	1.00	> 0.98	< 10%	<1.6
277		1	72	0.27	1.00	> 0.95	< 10%	<1.6
120	FC12T5-40W	2	80	0.65	.98	> 0.98	< 10%	<1.6
277		2	79	0.29	.98	> 0.98	< 10%	<1.6
120	CFM36W/2G10	2	68	0.57	.90	> 0.95	< 10%	<1.7
277		2	67	0.25	.90	> 0.95	< 10%	<1.7
120	CFM36W/2G10	1	33	0.28	.98	> 0.99	< 15%	<1.7
277		1	33	0.14	.98	> 0.90	< 15%	<1.7
120	CFTR32W	2	69	0.58	1.00	> 0.98	< 10%	<1.6
277		2	67	0.26	1.00	> 0.98	< 10%	<1.6
120	CFS28W	2	64	0.54	1.00	> 0.97	< 10%	<1.6
277		2	63	0.24	1.00	> 0.97	< 10%	<1.6
120	CFQ/TR26W	2	56	0.46	1.02	> 0.95	< 10%	<1.6
277		2	55	0.20	1.02	> 0.95	< 10%	<1.6
120	FT36W/2G11	2	64	0.43	.83	> 0.99	< 10%	<1.7
277		2	64	0.19	.83	> 0.97	< 10%	<1.7
120	FT24W/2G11	2	51	0.43	1.02	> 0.95	< 10%	<1.7
277		2	50	0.19	1.02	> 0.95	< 10%	<1.7
120	FT55W/2G11	1	46	0.38	.83	> 0.99	< 10%	<1.7
277		1	46	0.17	.83	> 0.95	< 10%	<1.7
120	FC9T5-22W	2	50	0.42	1.05	> 0.95	< 10%	<1.7
277		2	50	0.19	1.05	> 0.95	< 10%	<1.7
120	FC9T5-22W & FC12T5-40W	1 & 1	66	0.54	.98	> 0.97	< 10%	<1.7
277			64	0.24	.98	> 0.97	< 10%	<1.7
120	FC12T5-55W	1	44	0.36	.83	> 0.99	< 10%	<1.7
277		1	43	0.17	.83	> 0.93	< 10%	<1.7

- 'M' Enclosure Overall Dimensions
- Unit Weight
- Minimum Operating Temperature
- Maximum Operating Temperature
- EMI / RFI Compliance
- Sound Rating
- UL / CUL Listed
- Plug in wire connectors
- Chassis material Brushed Aluminum

4.89" L x 3.00" W x 1.20" H
 9 oz.
 Min. Enclosure Temp -20°C
 Max. Enclosure Temp 90°C
 FCC 47 CFR Part 18
 Rated 'A'
 File #E201562

