

UNIVERSAL INPUT 36W/39W FLUORESCENT SPECIFICATIONS (SINGLE LAMP / LOW PROFILE CHASSIS)

INPUT	MODEL PS30U92L
● Lamp Type & Wattage (4-Pin)	One 36W PLL, 39W PLL
● Vac	90 to 300
● Amps	0.28A @ 39W @ 120Vac & 0.12A @ 277Vac
● Frequency	60Hz
● Crest Factor	ANSI 62.41 CAT.A
● Power Factor	.98
● Ballast Factor	.95

OUTPUT	
● Lamp Drive Frequency	51kHz Sinusoidal
● Lamp Current Crest Factor	<1.4
● Programmed Pre-Heat Time	1.0 - 1.5 sec.
● UL Class 'P' Listed Type 1	Yes
● Ignition Failure Shutdown	Yes
● End of Lamp Life Protection	Yes

MECHANICAL / ENVIRONMENTAL

- Enclosure Overall Dimensions 5.57" L x 1.80" W x 1.02" H
- Unit Weight 6 oz.
- Minimum Operating Temperature Min. Enclosure Temp -30°C
- Maximum Operating Temperature Max. Enclosure Temp 90°C
- EMI / RFI Compliance FCC 47 CFR Part 18 non-consumer
- Sound Rating Rated 'A'
- UL / CUL Listed File #E201562
- All Wires are UL 1015 18ga. Solid, 18 inches in length.
- Chassis material is 0.040" Gray Anodized Aluminum..
- Ballast Efficiency >87%

