



DESCRIPTION

The LB with fully acrylic optics is a specification grade product for commercial and industrial lighting where a greater amount of vertical surface illumination is needed. U.L. damp location listed.

APPLICATION

Suitable for use in commercial areas such as grocery stores and retail outlets where product is being merchandised. Can also be used in industrial areas where greater light levels on vertical surfaces is desired.

HOUSING

The housing is made of high pressure die cast aluminum and finished in a white polyester powder coat paint finish for lasting corrosion resistance.

BALLAST

High Power Factor, Constant Wattage Autotransformer ballasts. Multi Tap (120/208/240/277V) or 480V ballasts. Minimum starting temperature is -20°F (-30°C) for MP and MH, -40°F (-40°C) for HPS.

SOCKET

Mogul base, 4KV pulse rated porcelain socket.

MOUNTING

Junction box and hook with safety screw included. 3/4" threaded opening on the top of the junction box for pendant mounting.

REFRACTOR

16" or 22" acrylic refractor with an acrylic drop dish.

CATALOG NUMBER LOGIC

LB-

Product Series
 LB = Low Bay

MP

Lamp Type
 MP = Metal Halide Pulse Start
 MH = Metal Halide
 HP = High Pressure Sodium

400-

Lamp Wattage
 (MP) 200, 250, 320, 350, 400
 (MH) 175, 250, 400
 (HPS) 150, 250, 400

MT-

Voltage
 MT = Multi Tap (120/208/240/277V)
 480V = 480V

ACDA22-

Refractor
 ACDA16 = Acrylic refractor with Drop Acrylic dish.
 ACDA22 = 22" version (for 400 W)

L

Lamp
 L = Lamp Included

OPTIONS

Q – Quartz restrike system with quartz restrike lamp
 QT – Quartz restrike system with time delay, with quartz restrike lamp.
 3CP-XXX – 3 foot Cord and NEMA Plug, XXX = specify voltage, 120 or 277V
 F1-XXX or F2-XXX – Single or Double Fuse. XXX = specify voltage.
 SC3 – Safety Cable 3'.